

**Tanvi Mines & Minerals**  
**303, Unnati Tower, Central Spine, Vidyadhar Nagar,**  
**Jaipur, Rajasthan, India**

**Material Safety Data Sheet Of Silica sand**

---

I. PRODUCTION IDENTIFICATION

---

**Trade Name :** Silica – Granules, Powder, Lumps

**Chemical Name and Formula:** Silica, in the form of quartz; SiO<sub>2</sub>

---

II. HAZARDOUS INGREDIENTS

---

**Chemical Name:** Quartz : %SiO<sub>2</sub> +2 particles 10 microns or smaller)

The exposure limits are time-weighted average concentrations for an eight-hour workday and a 40-hour work week.

Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C, it can change to a form of crystalline silica known as tridymite, and if crystalline silica (quartz) is heated to more than 1470°C, it can change to a form of crystalline known as cristobalite. The OSHA PEL for crystalline silica as tridymite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

---

III. HAZARD IDENTIFICATION

---

**Emergency Overview:** The crystalline silica produced by The Parry Company material is a white or tan, and is primarily used as water filter media. It is not flammable, combustible, or explosive. It does not cause burns or severe skin or eye irritation. A single exposure will not result in serious adverse health effects. Crystalline silica (quartz) is not known to be an environmental hazard. Crystalline silica (quartz) is incompatible with hydrofluoric acid, fluorine, chlorine trifluoride or oxygen difluoride.

**Potential Health Effects:**

**Silicosis:** Respirable crystalline silica (quartz) may cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death.

**Cancer:** Crystalline silica (quartz) inhaled from occupational sources is classified as carcinogenic to humans.

**Autoimmune Diseases:** There are some studies that show excess numbers of cases of scleroderma and other connective tissue disorders in workers exposed to respirable crystalline silica.

**Tuberculosis:** Silicosis increase the risk of tuberculosis.

**Nephrotoxicity:** There are some studies that show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.\

**Eye Contact:** Crystalline silica (quartz) may cause abrasion of the cornea.

**Skin Contact:** Not applicable

**Ingestion:** Not applicable.

**Chronic Effects:** The adverse health effects-silicosis, cancer, autoimmune diseases, tuberculosis, and nephrotoxicity-are chronic effects.

**Signs and Symptoms of Exposure:** Generally, there are no signs or symptoms of exposure to crystalline silica (quartz).

**Medical Conditions Generally Aggravated by Exposure:** The condition of individuals with lung disease (e.g., bronchitis, emphysema, chronic obstructive pulmonary disease) can be aggravated by exposure. Toxicological Information, for additional detail on potential adverse health effects.

---

#### IV. FIRST AID MEASURES

---

##### **Symptoms of Overexposure:**

**Inhaled:** Shortness of breath, coughing, reduced pulmonary function. Prolonged inhalation of respirable silica may result in permanent lung damage, silicosis. No specific first aid is necessary since the adverse health effects associated with exposure to crystalline silica (quartz) result from chronic exposures. If there is a gross inhalation of crystalline silica (quartz), remove the person immediately to fresh air, give artificial respiration as needed, seek medical attention as needed.

**Swallowed:** May cause gastrointestinal discomfort. Give one or two glasses of water. If discomfort persists, see a physician.

**First Aid:** Emergency procedures.

**Eye Contact:** Wash with water for at least fifteen (15) minutes. If irritation or redness persists see a physician.

**Skin Contact:** Wash with soap and water. If irritation persists see a physician.

**Ingestion:** Not applicable.

---

#### V. FIRE FIGHTING MEASURES

---

Crystalline silica (quartz) is not flammable, combustible, or explosive.

---

#### VI. ACCIDENTAL RELEASE MEASURES

---

**Spill Response Procedures (including employee protection measures):** Clean up using approved, dustless methods (water or vacuum) to minimize generation of respirable silica particles.

**Waste Disposal:** Dispose of in a facility approved for silica (also see Section 13).

---

#### VII. HANDLING AND STORAGE

---

**Ventilation and Engineering Controls:** Local mechanical to reduce respirable silica to below safe levels.

**Respiratory Protection (Type):** Use NIOSH approved equipment. Positive pressure supplied air-type recommended. Appropriate respiratory protection for respirable particulates is based on consideration of air borne workplace concentrations and duration of exposure arising from the intended end use. Please

refer to the most recent standards of ANSI (Z88.2), OSHA (29CFR 1910.134), MSHA (30 CFR Parts 56 & 57), and NIOSH RDL. IF you are unsure as to the type of respirator to be used please consult your employer.

**Eye Protection (Type):** Safety Glasses

**Gloves (Specify Material):** Not normally required.

**Other Protective Clothing and Equipment:** Not normally required.

**Work Practices, Hygiene Practices:** Clean up spills promptly. Do not engage in activities that will generate respirable silica particles.

**Other handling and Storage Requirements:** Avoid generating dust. There are no special storage requirements. Train all exposed persons in all sections of this MSDS and the proper handling of silica before they work with this product.

See OSHA Hazard Communication Rule CFR 1910.1200, 1915.99, 1917.28 and 1928.21, state, local worker, or community "Right to Know" laws and regulations. We recommend that smoking be prohibited in all areas where respirators must be used. Warn your employees (and your customer users in case of resale) by posting and other means of the hazard and OSHA precautions to be used. Provide training about the OSHA precautions. See control measures in Section 8.

#### VIII. EXPOSURE CONTROL/PERSONAL PROTECTION

Local Exhaust: Use sufficient local exhaust to reduce the level of respirable crystalline silica to below the PEL. See ACGIH "Industrial Ventilation, A Manual of Recommended Practice" (latest edition).

Respiratory Protection: The following chart specifies the types of respirators, which may provide respiratory protection for crystalline silica:

PARTICULATE CONCENTRATION	MINIMUM RESPIRATORY PROTECTION*
10 x PEL or Less	Any particulate respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
50 x PEL or Less	A high efficiency particulate filter with a full-face piece. Any supplied-air respirator with a full-face piece, helmet, or hood. Any self-contained breathing apparatus with a full-face mask.
500 x PEL or Less	A type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 500 x PEL or Entry and Escape from Unknown Concentrations	Self-contained breathing apparatus with a full-face piece operated in pressure-demand mode. A combination respirator which includes a Type C supplied-air respirator with a full-face piece operated in pressure-demand or other positive pressure continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.

**Use only NIOSH-approved or MSHA-approved equipment. See 29 CFR § 1910.134 and 42 CFR § 84. See also ANSI standard Z88.2 (latest revision) "American National Standard for Respiratory Protection."**

**Exposure Guidelines:**

Component	CAS No.	Percentage (by wt.)	OSHA (TWA)	OSHA (STEL)	ACGIH (TWA)	ACGIH (STEL)	NIOSH (TWA)	NIOSH (STEL)	Unit
Crystalline Silica (Quartz)	1480 8-60-7	99.0-99.9	$\frac{10}{\% \text{ SiO}_2 + 2}$	None	.05	None	.05	None	Mg/m <sup>3</sup>

---

IX. PHYSICAL AND CHEMICAL PROPERTIES

---

**Vapor Density:** Not applicable**Specific Gravity:** 2.65**Solubility in Water:** Insoluble**Vapor Pressure:** 10mm @ 1730°C**Melting Point:** 1710°C**Boiling Point:** 2230°C**Evaporation Rate:** None**Appearance and Color:** White to tan; odorless

---

X. STABILITY AND REACTIVITY

---

**Stability:** Stable**Hazardous Polymerization:** Will not occur**Incompatibility (materials to avoid):** Contact with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, oxygen difluoride.**Hazardous Decomposition Products:** Silica will dissolve in hydrofluoric acid and produce a corrosive gas (silicon tetrafluoride).

---

XI. TOXICOLOGICAL INFORMATION

---

**Silicosis:** The major concern is silicosis, caused by inhalation and retention of respirable crystalline silica dust. Silicosis can exist in several forms, chronic (or ordinary), accelerated, or acute.

**Chronic or Ordinary Silicosis (often referred to as Simple Silicosis)** is the most common form of silicosis, and can occur after many years of exposure to relatively low levels of airborne respirable crystalline silica dust. It is further defined as either simple or complicated silicosis. Lung lesions (shown as radiographic opacities) less than 1 centimeter in diameter characterize simple silicosis, primarily in the upper lung zones. Often, simple silicosis is not associated with symptoms, detectable change in lung function or disability. Simple silicosis may be progressive and may develop into complicated silicosis or progressive massive fibrosis (PMF). Complicated silicosis or PMF is characterized by lung lesions (shown as radiographic opacities) greater than 1 centimeter in diameter. Although there may be no symptoms associated with complicated silicosis or PMF, the symptoms, if present, are shortness of breath, wheezing, cough and sputum production. Complicated silicosis or PMF may lead to death. Advanced complicated silicosis or PMF can result in heart disease secondary to the lung disease (cor pulmonale).

**Accelerated Silicosis** can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; the lung lesions can appear within five (5) years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that the lung lesions appear earlier and the progression is more rapid.

**Acute Silicosis** can occur with exposures to very high concentrations of respirable crystalline silica over a very short period of time, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

**Cancer:**

**IARC:** The International Agency of Research on Cancer (IARC) concluded that there was “sufficient evidence in humans for the carcinogenicity of crystalline silica in the forms of quartz and cristobalite from occupational sources”, and that there is “*sufficient evidence* in experimental animals for the carcinogenicity of quartz and cristobalite.” The overall IARC evaluation was that “crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is *carcinogenic to humans (Group 1)*.” The IARC evaluation noted that “carcinogenicity was not detected in all industrial circumstances studies. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs.” For further information on the IARC evaluation, see IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 68, “Silica, Some Silicates...” (1997).

**NTP:** The National Toxicology Program, in its Ninth Annual Report on Carcinogens, classified “silica, crystalline (respirable)” as a known human carcinogen.

**OSHA:** Crystalline silica (quartz) is not regulated by the US Occupational Safety and Health Administration as a carcinogen.

There have been many articles published on the carcinogenicity of crystalline silica, which the reader should consult for additional information. The following are examples of recently published articles:

**Autoimmune Diseases:** There is evidence that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis is associated with the increased incidence of several autoimmune disorders, -scleroderma, systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. For a review of the subject, the following may be consulted:

**Tuberculosis:** Individuals with silicosis are at increased risk to develop pulmonary tuberculosis, if exposed to persons with tuberculosis. The following may be consulted for further information:

**Kidney Disease:** There is evidence that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis is associated with the increased incidence of kidney diseases, including end stage renal disease. For additional information on the subject, the following may be consulted:

---

## XII. ECOLOGICAL INFORMATION

Crystalline silica (quartz) is not known to be ecotoxic; i.e., there is no data that suggests that crystalline silica (quartz) is toxic to birds, fish, invertebrates, microorganisms or plants. For additional information on crystalline silica (quartz), see Sections 9 (physical and chemical properties) and 10 (stability and reactivity) of this MSDS.

---

## XIII. DISPOSAL CONSIDERATIONS

**General:** The packaging and material may be land filled; however, material should be covered to minimize generation of airborne dust.

**RCRA:** Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 et. seq.

The above applies to materials as sold by Fairmount Minerals, LTD. The material may be contaminated during use, and it is the responsibility of the user to assess the appropriate disposal of the used material.

---

---

XIV. TRANSPORT INFORMATION

---

Crystalline silica (quartz) is not a hazardous material for purposes of transportation under the US Department of Transportation Table of Hazardous Materials, 49 CFR §172.101.

---

XV. REGULATORY INFORMATION

---

**United States (Federal and State):**

**TSCA No:** Crystalline silica (quartz) appears on the EPA TSCA inventory under the CAS No. 14804-60-7.

**RCRA:** Crystalline silica (quartz) is not classified as hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 et seq

**CERCLA:** Crystalline silica (quartz) is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR §302.

**Emergency Planning and Community Right to Know Act:** Crystalline silica (quartz) is not an extremely hazardous substance under Section 302 and is not a toxic chemical subject to the requirements of Section 313.

**Clean Air Act:** Crystalline silica (quartz) mines and processed by Fairmount Minerals, Ltd. was not processed with or does not contain any Class I or Class II ozone depleting substances.

**FDA:** Silica is included in the list of substances that may be included in coatings used in food contact surfaces, 21 CFR §175.300 (b) (3) (xxvi).

**NTP:** Respirable crystalline silica (quartz) is classified as a carcinogen.

**OSHA Carcinogen:** Crystalline silica (quartz) is not listed.

**Canada:**

**Domestic Substances List:** Fairmount Minerals, Ltd's products, as naturally occurring substances, are on the Canadian DSL.

**WHMIS Classification:** D2A

**Other:**

**EINECS No:** 238-878-4

**EEC Label (Risk/Safety Phrases):** R 48/20, R 40/20, S22, S38

**IARC:** Crystalline silica (quartz) is classified in IARC Group I.

National, state, provincial or local emergency planning, community right-to-know or other laws, regulations or ordinances may be applicable—consult applicable national, state, provincial, or local laws.

---

XVI. OTHER INFORMATION

---

**H.M.I.S. Rating:**

Health Hazard Rating	1*	Flammability Hazard Rating	0
Reactivity Hazard Rating	0	Personal Protective Equipment	E**

**DOT:** Not Regulated

**SARA Title III:** Not listed.

\*Chronic exposure to respirable size silica will result in silicosis. \*\*Comply with special OSHA respiratory protection if sandblasting.